

HSG9680

NO.	DESCRIPTION
1	SCREW ST3X14
2	CHASSIS
3	DUST COVER
4	DUST PROOF COTTON
5	VDE PLUG & CABLE (WITH SHEATH)
6	INTERNAL WIRE
7	SMALL CIRCULAR SWITCH
8	CAPACITOR 0.22 μF
9	TERMINAL
10	MOTOR SEALING GASKET A
11	MOTOR
12	DECORATIVE STRIPS
13	CASING
14	WIND COLLECTION BUCKET
15	LOCK BUTTON STEEL WIRE
16	LOCK BUTTON
17	OUTER SEALING RING
18	WRENCH
19	ADJUSTING ROD PIN
20	SCREEN PRINTING BLOCK
21	ONLINE ROLLING FLOWER SET
22	ALUMINUM SLEEVE FOR ADJUSTING KNOB
23	GEAR FILM
24	LIMIT SCREW
25	GEAR STEEL BALL
26	GEAR SPRING
27	ADJUSTING ROD SPRING
28	COPPER ADJUSTMENT ROD
29	SEALING RING
30	TIGHTEN THE NUT
31	SPRAY HEAD
32	Φ 2.0 COPPER NOZZLE
33	TRANSPARENT CHANNEL
34	GUN BODY
35	SEALING RING
36	ANTI BACKFLOW PAD
37	STRAW COMPONENTS
38	SPRAY BOTTLE SEALING RING
39	SPRAY POT (1200)

HSG9680-EX-RU240816-1

